

SE-D

Signal Tower



LED



85dB at 1m
(FB type)

Electronic Sound 2
(FB type)

Ø57

IP54 (FB type: IP23)
(Pole mount: IP23)

NPN/PNP
Open collector




Signal Tower featuring enhanced visibility with original reflection system.

- PATLITE's Exclusive Hybrid Prism Cut Lens: For enhanced visibility from any direction and distance.
- Original LED reflection system: Improves brightness and provides maintenance free operation.
- FB type: 2 tone built-in buzzer with volume control (85dB at 1m).
- Installation: Direct or pole mount.
- Color-coordinated wiring: Corresponds to the lens color for quick wiring verification.
- Interchangeable LED module: No re-wiring even after installation.
- Lens: Weather resistant and light translucent AS resin.
- NPN/PNP compatible: Except 100/220V AC, compatible with NPN only.
- CE Compliance: 24V AC/DC type ONLY.
- Available Colors: Red, Amber, Green, Blue, Clear/White.

Available by Special Order

- UL type (E215660).
- RoHS compliance.

Dimensions



Wiring Diagram

Note: See page 171 for wiring diagram

SE-D Type

Number of Stacks	Model	Rated Voltage	Power Consumption
1 Light	SE-102D	24V AC/DC	1.5W
	SE-110D	100V AC	3.0W
	SE-112D	120V AC	3.5W
	SE-120D	220V AC	3.5W
2 Lights	SE-202D	24V AC/DC	2.5W
	SE-210D	100V AC	5.0W
	SE-212D	120V AC	5.5W
	SE-220D	220V AC	5.5W
3 Lights	SE-302D	24V AC/DC	3.5W
	SE-310D	100V AC	6.5W
	SE-312D	120V AC	7.0W
	SE-320D	220V AC	7.0W
4 Lights	SE-402D	24V AC/DC	4.5W
	SE-410D	100V AC	7.5W
	SE-412D	120V AC	8.5W
	SE-420D	220V AC	8.5W
5 Lights	SE-502D	24V AC/DC	5.5W
	SE-510D	100V AC	8.5W
	SE-512D	120V AC	10.0W
	SE-520D	220V AC	10.0W

How to Order

