## **SPECIFICATIONS**

Model		CLF10-24-		
Color of lighting		R(Red), Y(Amber), C(White)		
Light source		4-LED		
Rated voltage		24V DC (non-polar)		
Operating voltage		Rated voltage±10%		
Current consumption		104mA±10mA		
Operating temperature range (Relative humidity)		-30°C∼+60°C (90%RH or less, without the dew condensation)		
Mounting	Place	Indoor only		
	Direction	Any direction		
Protection rating		IP67		
Vibration proof		19.6 m/s <sup>2</sup> (30Hz)		
Illumination at the center(at 50cm)		Red:240lx, Amber:320lx, White:850lx		
Mass		205g±10g		

## No.CLF10-24-A18A-1/2

- This product confirms to the CE requirements and CE Marking is indicated.
- This product complies with the RoHS Directive(DIRECTIVE 2002/95/EC)
- Model No. configuration



		App.by	Chk.by	Drn.by
PATLITE	Corporation	HENIU 8 Feb 08		July game

## **SPECIFICATIONS**

Model		CLF20-24-		
Color of lighting		R(Red), Y(Amber), C(White)		
Light source		8-LED		
Rated voltage		24V DC (non-polar)		
Operating voltage		Rated voltage±10%		
Current consumption		208mA±20mA		
Operating temperature range (Relative humidity)		-30°C∼+60°C (90%RH or less, without the dew condensation)		
Mounting	Place	Indoor only		
	Direction	Any direction		
Protection rating		IP67		
Vibration proof		19.6 m/s <sup>2</sup> (30Hz)		
Illumination at the center(at 50cm)		Red:471lx, Amber:630lx, White:1700lx		
Mass		345g±10g		

## No.CLF20-24-A18A-1/2

- ●This product confirms to the CE requirements and CE Marking is indicated.
- This product complies with the RoHS Directive(DIRECTIVE 2002/95/EC)
- Model No. configuration



	App.by	Chk.by	Drn.by
PATLITE Corporation	Konji)		Nicojana 6 Rab'os