



6ES7214-1BE30-0XB0 CPU 1214C 14DI/10DO/2AI

Technical / CAx data

☒ Technical Data ☐ CAx data

SIMATIC S7-1200, CPU 1214C, COMPACT CPU, AC/DC/RLY, ONBOARD I/O: 14 DI 24V DC; 10 DO RELAY 2A; 2 AI 0 - 10V DC, POWER SUPPLY: AC 85 - 264 V AC AT 47 - 63 HZ, PROGRAM/DATA MEMORY: 50 KB

Product version
associated programming package STEP 7 Basic V10.5

Supply voltages
Rated value

120 V AC	Yes
230 V AC	Yes
permissible range, lower limit (AC)	85 V
permissible range, upper limit (AC)	264 V
permissible frequency range, lower limit	47 Hz
permissible frequency range, upper limit	63 Hz

Load voltage L+

Rated value (DC)	24 V
permissible range, lower limit (DC)	5 V
permissible range, upper limit (DC)	250 V

Current consumption

Current consumption (rated value)	100 mA @ 120 VAC 50 mA @ 240 VAC
Current consumption, max.	300 mA @ 120 VAC 150 mA @ 240 VAC
Inrush current, max.	20 A; At 264 V
Current output to backplane bus (DC 5 V), max.	1600 mA; 5 VDC max. for SM and CM

Power losses

Power loss, typ.	14 W
-------------------------	------

Memory

Usable memory for user data	50 kbyte
------------------------------------	----------

Work memory

integrated	50 kbyte
expandable	No

Load memory

integrated	2 Mbyte; Load memory expandable using SIEMENS Memory Card
expandable, max.	24 Mbyte; with SIEMENS Memory Card

Backup

present	Yes; entire project maintenance-free in the integral EEPROM
without battery	Yes

CPU/ blocks
OB

Number, max.	Limited only by RAM for code
---------------------	------------------------------

CPU processing times

for bit operations, min.	0.1 µs; / instruction
---------------------------------	-----------------------

for word operations, min.	12 µs; / instruction
for floating point arithmetic, min.	18 µs; / instruction
Data areas and their retentivity	
retentive data area in total (incl. times, counters, flags), max.	2048 byte
Flag	
Number, max.	8 kbyte; Size of bit memory address area
Address area	
I/O address area	
I/O address area, overall	1024 bytes for inputs / 1024 bytes for outputs
Inputs	1024 byte
Outputs	1024 byte
Process image	
Inputs, adjustable	1 kbyte
Outputs, adjustable	1 kbyte
Digital channels	
integrated channels (DI)	14
integrated channels (DO)	10
Analog channels	
Integrated channels (AI)	2
Number of integrated channels (AO)	0
Hardware configuration	
Number of modules per system, max.	3 comm. modules, 1 signal board, 8 signal modules
Time of day	
Clock	
Hardware clock (real-time clock)	Yes
Backup time	240 h; Typical
Deviation per day, max.	60 s/month @ 25 °C
Test commissioning functions	
Status/control	
Status/control variable	Yes
Variables	Inputs/outputs, memory bits, DB, distributed I/Os, timers, counters
Forcing	
Forcing	Yes
Communication functions	
S7 communication	
supported	Yes
as server	Yes
Open IE communication	
TCP/IP	Yes
ISO-on-TCP (RFC1006)	Yes
Number of connections overall	15; dynamically
1st interface	
Type of interface	PROFINET
Physics	Ethernet
Isolated	Yes
automatic detection of transmission speed	Yes

Autonegotiation	Yes
Autocrossing	Yes
CPU/ programming	
Configuration software	
STEP 7	STEP 7 Basic V10.5
Programming language	
LAD	Yes
FBD	Yes
Cycle time monitoring can be set	Yes
Digital inputs	
Number of digital inputs	14; Integrated
of which, inputs usable for technological functions	6; HSC (High Speed Counting)
m/p-reading	Yes
Input voltage	
Rated value, DC	24 V
for signal "0"	5 VDC at 1 mA
for signal "1"	15 VDC at 2.5 mA
Input current	
for signal "1", typ.	1 mA
Input delay (for rated value of input voltage)	
for standard inputs parameterizable	0.2, 0.4, 0.8, 1.6, 3.2, 6.4, and 12.8 ms, selectable in groups of four
at "0" to "1", min.	0.2 ms
at "0" to "1", max.	12.8 ms
for interrupt inputs parameterizable	Yes
Cable length	
Cable length, shielded, max.	500 m; 50 m for technological functions
Cable length unshielded, max.	300 m; For technological functions: No
Digital outputs	
Number of digital outputs	10; Relay
Short-circuit protection of the output	No; to be provided externally
Switching capacity of the outputs	
with resistive load, max.	2 A
on lamp load, max.	30 W DC; 200 W AC
Output delay with resistive load	
0 to "1", max.	10 ms; max.
1 to "0", max.	10 ms; max.
Switching frequency	
of the pulse outputs, with resistive load, max.	1 Hz
Cable length	
Cable length, shielded, max.	500 m
Cable length unshielded, max.	150 m
Relay outputs	
Number of relay outputs	10
Number of operating cycles	mechanically 10 million, at rated load voltage 100,000
Analog inputs	
Number of analog inputs	2

Cable length, shielded, max.	100 m; twisted and shielded
Input ranges	
Voltage	Yes
Input ranges (rated values), voltages	
0 to +10 V	Yes
Input resistance (0 to 10 V)	≥100k ohms
Analog outputs	
Cable length	10 m; twisted
Analog value creation	
Integrations and conversion time/ resolution per channel	
Resolution with overrange (bit including sign), max.	10 bit
Integration time, parameterizable	Yes
Conversion time (per channel)	625 μs
Encoder supply	
24 V encoder supply	
24 V	permissible range: 20.4 to 28.8 V
Encoder	
Connectable encoders	
2-wire BEROs	Yes
Integrated Functions	
Number of counters	6
Counter frequency (counter) max.	100 kHz
Frequency meter	Yes
controlled positioning	Yes
PID controller	Yes
Number of alarm inputs	4
Operator control and monitoring	
Display	No
Galvanic isolation	
Galvanic isolation digital inputs	
Galvanic isolation digital inputs	500 VAC for 1 minute
between the channels, in groups of	1
Galvanic isolation digital outputs	
Galvanic isolation digital outputs	Relays
between the channels	No
between the channels, in groups of	2
Permissible potential difference	
between different circuits	500 VDC between 24 VDC and 5 VDC
EMC	
Interference immunity against discharge of static electricity	
Interference immunity against discharge of static electricity acc. to IEC 61000-4-2	Yes
	8 kV
Test voltage at contact discharge	6 kV
Interference immunity to cable-borne interference	

on the supply lines acc. to IEC 61000-4-4	Yes
Interference immunity on signal lines acc. to IEC 61000-4-4	Yes
Surge immunity	
on the supply lines acc. to IEC 61000-4-5	Yes
Immunity against conducted interference induced by high-frequency fields	
Interference immunity against high-frequency radiation acc. to IEC 61000-4-6	Yes
Emission of radio interference acc. to EN 55 011	
Emission of radio interferences acc. to EN 55 011 (limit class A)	Yes; Group 1
Emission of radio interference acc. to EN 55 011 (limit class B)	Yes
Climatic and mechanical conditions for storage and transport	
Climatic conditions for storage and transport	
Free fall	0.3 m; five times, in dispatch package
Temperature	
Permissible temperature range	-40 °C to +70 °C
Relative humidity	
Permissible range (without condensation) at 25 °C	95%
Mechanical and climatic conditions during operation	
Climatic conditions in operation	
Temperature	5 °C to 55°, 3 °C/minute
Air pressure acc. to IEC 60068-2-13	
Permissible air pressure	1080 to 795 hPa
Permissible operating height	-1000m to 2000m
Pollutant concentrations	SO ₂ : < 0.5 ppm; H ₂ S: < 0.1 ppm; RH < 60% condensation-free
Environmental requirements	
Operating temperature	
Min.	0 °C
max.	55 °C
vertical installation, min.	0 °C
vertical installation, max.	45 °C
horizontal installation, min.	0 °C
horizontal installation, max.	55 °C
Storage/transport temperature	
Min.	-40 °C
max.	70 °C
Air pressure	
Operation, min.	795 hPa
Operation, max.	1080 hPa
Storage/transport, min.	660 hPa
Storage/transport, max.	1080 hPa
Relative humidity	

Operation, max.	95 %; no condensation
Vibrations	
Vibrations	2G panel mount, 1G DIN rail mount
Operation, checked according to IEC 60068-2-6	Yes
Shock test	
checked according to IEC 60068-2-27	Yes; 15 G, 11 ms pulse, 6 shocks in each of 3 axes
Degree of protection	
IP20	Yes
Standards, approvals, certificates	
CE mark	Yes
C-TICK	Yes
cULus	Yes
FM approval	Yes
Dimensions and weight	
Dimensions	
Width	110 mm
Height	100 mm
Depth	75 mm
Weight	
Weight, approx.	455 g
Status	Jun 14, 2010