
## Gh robot

End-of-arm Tooling and Accessories for All Collaborative Applications



## Choosing the right robot accessories


Light industrial robots will become a commodity, and focus will shift towards end-of-arm tools such as grippers and sensors




# The right robot accessories simplify changeovers and give you flexibility in your production











#### Purchase

The right tools for the intended materials and tasks

#### Installation

User-friendly installation minimizes disruption to ongoing production

## Programming

Intuitive programming gets the robots up and running quickly


## Operations

Human operators and robots work safely side-by-side

## Redevelopment

Flexible and seamless switching across multiple tasks as needed

## The right robot accessories revolutionize automation




## Flexible and Easy to Deploy

One tool can switch between multiple tasks with minimal need for additional programming or tool swapping



#### Increase Production

Robotic tools work around the clock completing tasks with greater precision and reliability than human operators




Lower Automation Costs

Safe, collaborative and intelligent tools work in close proximity to human operators without additional safety fencing, programming or installation costs

# Chrobot




Tools for all collaborative and light industrial robotic automation systems




## Our Vision

Building a one stop shop for enabling collaborative applications


An extensive range of products that cover:



All Robots



All Applications



All Accessory Types



All Industries

## A Growing Suite of Solutions

OnRobot brings together technical expertise and key innovations from technological leaders in the robotics industry



#### Founded in 2015

Plug-and-produce electric grippers



#### Founded in 2012

Multi-axis force torque sensors



## Formed via merger in June 2018

Growing suite of robot accessories and solutions



#### Founded in 2012

Grippers equipped with tactile sensor technology inspired by nature.



#### Founded in 2017

Electric vacuum grippers and manual tool changers

## Growing With OnRobot

OnRobot will continue to expand its capabilities further through research and development, and mergers with industry-leading companies



## Building a Trusted Global Brand

Cutting-edge robotic solutions across the globe



0 0 0 0 0 0 0 0

0 0 0 0 0 0 0

0 0 0 0 0 0 0

0 0 0 0 0 0 0

0 0 0 0 0 0

0 0 0 0 0







0 0 0 0


## Making Automation Accessible

OnRobot's suite of intelligent accessories lowers the barrier to automation for businesses of every size and industry



## One-Stop Shop For All Tools

Customers can purchase an extensive range of robot accessories and software in one place



## Easy Deployment

OnRobot's robot accessories are designed to work with an extensive and ever-expanding range of robot brands with minimal compatibility issues and need for complicated engineering



## Intelligent Operations

Easy programming and intelligent tool technologies enable greater precision, reliability and productivity growth




## One-Stop Shop For All Tools:

Meet all your collaborative automation needs with OnRobot



## Comprehensive Range of Tools

OnRobot offers a range of tools across functions and types to meet different production needs




## Compatibility

OnRobot tools can be integrated with several existing robot systems



## **Training Support** For Partners

OnRobot empowers partners with sales and product knowledge for greater customer engagement through partner training sessions



## Easy Deployment:

Get collaborative solutions up and running easily with OnRobot



## Plug and Produce

Ready to operate immediately upon unboxing and easily integrated into existing systems

## Easy Redeployment

Switch between tasks and accessories seamlessly with the Tool Changer or with our flexible grippers

## Simplified Programming

Our software tools make it fast to program a difficult application




## Intelligent Operations:

Power up production with added gripping and sensing capabilities

Two-way information exchange between tools and robots enables efficient operations

Instructions are programmed via robots and directed to robot tools



Our robot tools collect and feed data to the robot in real-time

# Chrobot



## **Our Products**

Intelligent tools and robot accessories for every automation need



## The OnRobot Product Universe

Everything you need to automate your production

**Tool Changing** Gripping Sensing
























## RG2/RG6

Plug & Produce gripper for multiple purposes



#### Features

Plug & Produce ready to go out of the box

Large stroke with forcebased gripping

Customizable fingertips



### Capabilities

Faster setup, less changeover time

Adaptive gripper with a very large stroke – it can just close until it feels enough force

The fingertips can be replaced fitting the product shape



#### Benefits

More flexible production with less down-time

Cost effective, can handle large variations in the process, same gripper for multiple purposes

Fast to start producing a new part







Fast installation and simple programming reduce deployment time by about 30%

## RG2/RG6 Applications

The RG2 can be used with products of various sizes and materials, including:





## Possible Applications Include:

Fragile objects



Wood


Packaging & Palletizing

Relieve workers of repetitive tasks



Pick and Place

Moving items from and onto conveyor belts



Machine Tending

CNC machine loading and unloading



Assembly

Assembly of smaller parts



## HEX F/T Sensor

Giving robots a sense of touch



#### **Features**

Force control software included

Easy-to-use advanced functions

Optical principle unique in the industry



## Capabilities

Can 'feel' if the object is in position, can correct robot's or part's imperfections

Programming within minutes: Difficult assembly, polishing, sanding, deburring

More robust sensor, IP67 rated



#### Benefits

Higher productivity, more stable and precise production

New automation possibilities with less cost

Durability – the sensor can resist sudden shock



Pre-programmed force sensing applications get you up and running quickly.

# HEX F/T Sensor Applications

The HEX F/T Sensor can be used with products of various sizes and materials, including:



Wood






Metals Pla



**Plastics** 



Fragile materials



### Possible Applications Include:



Assembly

Electronics, household appliances, automotive electronics



Surface Finishing
Deburring, Grinding,
Polishing



Quality Testing & Inspection
Precision, consistency



## RG2-FT Gripper

Intelligent gripper with a sense of sight and touch



#### Features

6 axis F/T Sensor built into gripper fingertips

Proximity sensor built into fingertips

Integrated forcecontrolled insertion software



## Capabilities

Detects location of the workpiece even if not precisely positioned

Gripper can see if its handed something and knows if you want it to release

Easy set-up and programming even for complicated tasks



#### Benefits

Increased efficiency and reduced damage risk

A real collaborative partner for your workforce

Greater precision in handling



The RG2 Gripper is the world's first intelligent gripper that can see and feel objects using built-in force/torque sensing

## RG2-FT Gripper Applications

The RG2-FT Gripper can be used with products of various sizes and materials, including:







Plastics

Metal

Packaging





Wood

Fragile objects

## Possible Applications Include:



Packaging & Palletizing

Relieve workers of repetitive tasks



#### Pick and Place

Moving items from and onto conveyor belts



#### Machine Tending

CNC machine loading and unloading



#### Assembly

Assembly of smaller parts



## GECKO GRIPPER

Gripping inspired by nature



#### **Features**



Special adhesive technology

In-built Proximity

sensor

Unique technology for pick and place flat and smooth objects



## Capabilities

No external air supply needed

Can detect part presence

Porous objects like PCB can be handled easily



#### Benefits

Faster setup, less running cost, less noise

More precise production


New automation possibilities



Using technology inspired by nature, it's possible to lift flat, smooth and even porous surfaces

## Gecko Gripper Applications

The GECKO GRIPPER can be used with products of various sizes and materials, including:






## Possible Applications Include:



Packaging & Palletizing

Relieve workers of repetitive tasks



Pick and Place

Moving items from and onto conveyor belts



## VG10 Vacuum Gripper

Flexible, adjustable electrical vacuum gripper



#### **Features**

Built-in electric vacuum

Dual gripping feature, A and B channels can be individually programmed

Variable vacuum gives you control



## Capabilities

No external air supply needed

Can handle 2 products simultaneously with the flexible adjustment of suction cup arms

Configurable suction cups



#### Benefits

Less running cost, less noise, takes up less space

Higher utilization of the robot,
Shorter cycle time, more output

Can accommodate 3rd party suction cups



Designed for collaborative robot applications – works straight out of the box

## VG10 Vacuum Gripper Applications

The VG10 VACUUM GRIPPER can be used with products of various sizes and materials, including:



Metal





Glass



Plastic



Glossy, Heavy Paper



## Possible Applications Include:



Packaging & Palletizing

Relieve workers of repetitive tasks



Pick and Place

Moving items from and onto conveyor belts



## Quick Changer

Click-on speed for fast tool changes




Features



Capabilities



Benefits





Short and easy changeover



More uptime, can quickly produce multiple, smaller orders

Smart Design



Can be coupled with a single click



Less down-time, easy redeployment



The easiest and fastest tool changer — click on your next tool and get back to production.





Customize your robot set-up with our range of accessories that work seamlessly together



## Object Handling

OnRobot's products work together to help you precisely handle objects of all shapes and sizes

## HEX-E F/T Sensor

Increases accuracy of grippers via force and torque measurements to detect the position of the parts

## Quick Changer

Lets you quickly switch between say, RG2 grippers and your vacuum gripper, or vice versa to meet ever-changing production needs

#### RG2 Gripper

Picks up and inserts parts with high accuracy and precision; can be replaced with other grippers depending on your product type. Fingertips can be customized to suit your needs.











## Finding The Right Gripper

No matter what your product is, there's a gripper to meet your production needs from OnRobot's range of interchangeable grippers

#### RG2-FT Gripper

For high-precision assembly type applications where F/T sensing in fingertips is required\*







Customize your robot set-up with our range of accessories




## Packaging & Palletizing

Make monotonous packaging and palletizing tasks a breeze with automation



#### **FLEXIBLE**

Adjustable force enables handling of fragile parts without risking damage



**PRECISION** 

High repeatability and precision with minimal error and wastage



#### **EFFICIENCY**

Increased production in collaborative applications via robots which run autonomously



ADDED VALUE

Employees freed from strenuous and repetitive tasks for other value-added work

## Packaging and Palletizing:

Packaging and palletizing of products of every size and shape

#### Force Torque Sensors

Detecting presence for greater accuracy



**HEX Sensor** 

#### Grippers

Picking up and moving objects with the right force and high flexibility



RG2/6 Gripper



**Dual Gripper** 



VG 10 Gripper




Gecko Gripper



## Surface Finishing

Accurate surface finishing with a sense of touch




#### Precision

Keeping predefined force and speed constant achieving accurate surface finishing



## Quality

Reliably follows any kind of difficult contour, robot will adapt to this surface



#### **Advanced Functions**

Software package allows short integration and easy programming

## Surface Finishing

## Force Torque Sensors

Controlling robot motion for the perfect results



**HEX Sensor** 

## Machine Tending

Increase productivity with dual grippers




## Faster Cycle Time

Higher CNC machine utilization: at least 50% faster



## Flexible Gripping

Same grippers can be used for different sized of objects



Easy Deployment

Fast conversion from one production line to another, quick changeover time

## Machine Tending

## **Dual Gripper**

Faster cycle time, faster payback



RG2, RG6 Dual Gripper



## Assembly

Locate and precisely grip objects of various shapes and sizes



#### **Precise Insertion**

Robot can easily find the right orientation with insertion software module



#### Real Collaboration

Can support workers as co-worker by handing the product to the human operators



## Flexible Gripping

Use the same gripper for objects of different sizes, materials and shapes simultaneously

## Assembly

## Force Torque Sensors

Precise insertion with a sense of touch



**HEX Sensor** 

## Grippers

Locate and precisely grip various shapes and sizes



RG2/6 Gripper



RG2-FT Gripper


## Quality Assurance

Ensure precision and consistency in your operation



## Predictable Quality

Ensuring consistent quality during production by keeping consistent force values




## Lower Operational Cost

Automating manual processes



Less Waste

Less raw materials wastage due to precise handling



Efficiency

Employees freed from strenuous or repetitive tasks for other value-added work

## Quality Testing and Inspection

## Force Torque Sensors

Automate testing that requires the sense of touch



**HEX Sensor** 





## Customer Success Stories

Cutting-edge robotics solutions for customers across sectors and industries



# Automating herb and flower packaging with Rosborg Food Holding

Rosborg Food Holdings is Denmark's largest herb producer. They cultivate an extensive range of herbs, flowers and plants in 120,000m2 of greenhouses.

#### **INDUSTRY:**



Farming

## Rosborg's CHALLENGE:



Large volumes of produce - up to 12 million mini flowers and 28 million herb plants need to be packaged annually



Plants are delicate and easily damaged in the packing process



# Automating herb and flower packaging with Rosborg Food Holding



#### Rosborg's SOLUTION

RG6 gripper that packages cut herbs and places them on the conveyor belt for packing



Gentle grip: Delicate plants are handled without being damaged



Highly Precise: Plants are packaged efficiently without waste or damage



Highly flexible: Able to work with packages of different sizes and weights on the same production line

### THE RESULTS:



Doubled production during peak sessions without profit loss → no need for extra people hire



Greenhouse workers freed from monotonous packing tasks

# Accelerating Production with Rosborg Food Holdings



# Enabling Round the Clock Production with Osvald Jensen

Osvald Jensen A/S is a market leader in developing and producing worm gears, wheels and custom gears at their facility in Denmark.

#### **INDUSTRY:**



**PACKAGING** 

### Osvald Jensen's CHALLENGE:




Increasing manpower to meet production needs is limited by the tight labor market and growing cost of labor



Loading CNC machines is a tedious task with a risk of human error when performed manually by operators



# Enabling Round the Clock Production with Osvald Jensen



#### OSVALD JENSEN'S SOLUTION

RG2 Dual Gripper that loads and unloads CNC machines



Double Gripping: Increases CNC machine productivity by handling two items simultaneously



Autonomous Operations: Grippers work around the clock to increase production volume even when human operators are not present



Reduced faults: Grippers work around the clock to increase production volume even when human operators are not present

### THE RESULTS:



Cycle time reduced by 40%, increasing productivity



ROI achieved in less than 3 months after implementation

# Accelerating Production with Osvald Jensen



# Accelerating Production with FT-Produktion

FT-Produktion is a family-owned machine shop supplying metal tools and parts to a diverse range of customers, including those in the automotive, construction and furniture industries. The company has an annual turnover of SEK 19 million and works with global manufacturers like Volvo, Renault and Scania.

#### **INDUSTRY:**




MANUFACTURING

### FT-PRODUKTION'S CHALLENGES:




Ability to meet rising production demands is restricted by a tight labor market and difficulty in recruiting qualified operators



Production runs range from five to 150,000 units, requiring frequent reconfiguration of production work flows



# Accelerating Production with FT-Produktion



#### **ONROBOT'S SOLUTION**

RG2 Dual Gripper that loads and unloads CNC machines



Double Gripping: Each gripper can load and unload a CNC machine simultaneously, cutting production cycle time by 12 seconds per task



Autonomous Operations: Grippers handle production tasks reliably with little error, enabling operators to manage multiple machines and take on a greater variety of tasks



Easy Redeployment: Grippers can be redeployed to work with different materials and tasks with minimal downtime

### THE RESULTS:



500 hours saved for the manufacture of every 150,000 parts



Operators freed of strenuous, tedious tasks to do value-added work

# Accelerating Production with FT-Produktion





The World's Leading
One-stop Shop for
Collaborative Solutions

onrobot.com

Contact us:

<insert email>



Appendix



## RG2 Gripper

	Minimum	Typical	Maximum	Units
Technical Data				
Total stroke Finger position resolution Repetition accuracy Reversing backlash	0 0,2	- 0,1 0,1 0,4	110 - 0,2 0,6	[mm] [mm] [mm] [mm]
Gripping force (adjustable) Gripping force accuracy	3 ± 0.05	- ± 1	40 ± 2	[N] [N}
Operating voltage* Power consumption Maximum current Ambient operating temperature	<ul><li>10</li><li>1,9</li><li>25</li><li>5</li></ul>	24 - -	26 14,4 600 50	[V DC] [W] [mA] [ºC]
Storage temperature Product weight	O -	- 0,65	60 -	[ºC] [kg]

<sup>\*</sup> At 12V, the Gripper runs at approximately half the normal speed

## RG6 Gripper

	Minimum	Typical	Maximum	Units
Technical Data				CHILS.
recifficat Data	-	54	_	
IP Class	0	_	160	-
Total stroke (adjustable)	-	0,15		[mm]
Finger position resolution	_	0,15	- 0.2	[mm]
Repetition accuracy	0,4	0,7	0,3	[mm]
Reversing backlash	•	,	1	[mm]
	25	-	120	Fo. 17
Gripping force (adjustable)	± 2	± 5	± 10	[N]
Gripping force accuracy			<u> </u>	[N}
	10	24	26	
Operating voltage*	1,9	_	14,4	[V DC]
Power consumption	25	_	600	[W]
Maximum current	5	_		[mA]
Ambient operating temperature			50	[00]
	0	_	60	
Storage temperature	_	0,1		[ºC]
Product weight		•	_	[kg]

<sup>\*</sup> At 12V, the Gripper runs at approximately half the normal speed

## RG-FT Gripper

	Minimum	Ту	pical	Maximum	
General Properties  Total stroke Finger position resolution Gripping force (adjustable)	0mm - 3N	- O.:	1mm	98mm - 40N	
Force Sensor  Nominal capacity (N.C)  Noise free resolution	Fxy 20N 0.1N	Fz 40N 0.4N	Txy 0.7Nm 0.008Nm	Tz 0.5Nm 0.005Nm	
Proximity Sensor Resolution	Minimum -		pical nm	Maximum -	

## Hex E FT Sensor

#### **Technical Specifications**

Target Value

## Pad Specifications

Dimensions (Height X Diameter)		37.5 x	70mm		
Weight (with built in adapter plates)	245g				
	Fxy	Fz	Txy	Tz	
Nominal Capacity (N.C)	200 N	200 N	10 Nm	6.5 Nm	
Single axis deformation at N.C (typical)	±1.7mm	±0.3mm	±2.5°	±5º	
Single axis overload	500%	500%	500%	500%	
C: 1 2	0.0051	0.451	0.0001	0.00411	

Single axis deformation at N.C (typical)	±1.7mm	±0.3mm	±2.5º	±5º
Single axis overload	500%	500%	500%	500%
Signal noise <sup>2</sup>	0.035N	0.15N	0.002Nm	0.001Nm
Noise-free resolution (typical)	0.2N	0.8N	0.010Nm	0.002Nm
Full scale nonlinearity	<2%	<2%	<2%	<2%
Hysteresis (measured on Fz axis, typical)	<2%	<2%	<2%	<2%
Crosstalk (typical)	<5%	<5%	<5%	<5%
Working temperature range		0 Cº / +55	ōC	

osstalk (typical)	<5%	<5%	<5%	<5%	
orking temperature range	0 Cº / +55 °C				
			W8.C		

Power requirement	DC input range 7 -24V		
Mounting screws	5x M4 x 6mm	ISO14581	
	1 x M4 x 12mm (for the cable holder)		

## Hex H FT Sensor

#### **Technical Specifications**

Tz

0 Cº / +55 °C

Target Value

## Pad Specifications

Working temperature range

Dimensions (Height X Diameter)		37.5	x 70mm	
Weight (with built in adapter plates)		245g		
	Fxy	Fz	Txy	
Nominal Capacity (N.C)	200 N	200 N	20 Nr	

			_	
Nominal Capacity (N.C)	200 N	200 N	20 Nm	13 Nm
Single axis deformation at N.C (typical)	± 0.6mm	± 0.25mm	± 2º	± 3.5°
Single axis overload	500%	400%	300%	300%
Signal noise <sup>2</sup>	0.1N	0.2N	0.006Nm	0.002Nm
Noise-free resolution (typical)	0.5N	1N	0.036Nm	0.008Nm
Full scale nonlinearity	<2%	<2%	<2%	<2%
Hysteresis (measured on Fz axis, typical)	<2%	<2%	<2%	<2%
Crosstalk (typical)	<5%	<5%	<5%	<5%

Power requirement	DC input range 7 -24V	0.8W
Mounting screws	5x M4 x 6mm	ISO14581
ivioariting serews	1 x M4 x 12mm (for the cable holds	er)

## Gecko Gripper

#### **Technical Specifications**

#### Value/Comments

### Pads

Change out interval
Autonomous cleaning system
Minimum run-time for cleaning
Autonomous cleaning interview and % recovery
Robotic cleaning system
Robotic cleaning interval and % recovery

100,000 to 200,000 cycles

Piezoelectric 1 second

15 sec: 3% / 2min: 5% / 15 min: 15% (max)

Silicone roller Variable / 100%

Sensors

Range Sensitivity **Pre-load Sensor** 

40 -140 N

3 N

**Ultrasonic Range Sensor** 

0 -260 mm 300 kHz

## VG10 Vacuum Gripper

	Minimum	Typical	Maximum	Units
Technical Data				
Vacuum  Air Flow Power Supply Current consumption* Operating temperature	5% -0.05% 1.5 0 20.4 50	- - - - 24 600	80% -0.810 24 12 28.8 1500 50	[Vacuum] [Bar] [inHg] [NI/min] [Volts] [mA] [ºC]
Reach	0 32 32	- -	122 358 14.09	[ºF] [mm] [in]
Adjustable arms Holding torque arms Payload	1.26 0 - 0	- 6 -	<ul><li>270</li><li>0</li><li>10</li><li>22</li></ul>	[*] [Nm] [kg] [lb]
Vacuum cups Gripping time Releasing time Foot-inch-foot	0 1 - -	- 0.35 0.20 1.40	16 - -	[pcs.] [s] [s]

## Quick Changer

	Minimum	Typical	Maximum	Units
Technical Data				
Permissible force Permissible torque Rated payload	_	_	400*	N
	_	_	50*	Nm
	_	-	10	Kg
	_	_	22	Lbs
Weight (robot-part)	_	0.062	_	Kg
		0.137		Lbs
Weight (tool-part)	_	0.140	_	Kg
	_	0.308	_	Lbs
Combined weight	_	0.202	_	Kg
		0.445		Lbs
Combined height	_	24.10	_	Mm
	_	0.95	_	In
Angle difference		22.5		Deg.
		0.3927		Rad.
Repeatability Tool Change Robot operation	_	_	±0.02	Mm
	_	5.000	_	Cycles
	10	-	-	M cycles

## Joining The OnRobot Ecosystem



## Established Global Network

Be a part of our diverse network, with customers across <number> countries and <number> industries globally



## Growing Customer Base

Tap into OnRobot's existing customer network and join our curated portfolio of products trusted by customers



## Supportive Partner

Access a full suite of product and industry knowledge, materials and tools through our partners' commercial and training support programs