Request Form - Timing Belt Conveyor

Customer Information					
Date:					
Company:					
Contact person:					
Telephone number:					
E-Mail address:					
Quotation submittal:					
Timing Belt Conveyor					
Number of conveyors [pcs]:					
Number of lanes [pcs]:					
Centre distance between lanes [mm]:					
Total length [mm]:					
Speed [m/min]:	Constant	Adjustable from to			
Speed controller:	Yes (unwired, supplied loose)	No			
Total load / conveyor [kg]:					
Side guides:	Yes	No			
† (**					
Height					
l l					
	₩				
Height [mm]:					
Ambient temperature [°C]:					
Material temperature [°C]:					
5: 1111					
Drive and Idler					
Standard voltage: Δ 230V /Y 400V, 50	Hz Special voltage:				
Cycle operation: Cycle/r	min Run time [s]	Distance [mm]			
Accumulation:	Yes	No			
Transport direction:	Pulling	Pushing			
Drive type:					
АВ	E F R S	OP			
Detailed description in our Robotunits catalogue, section ConveyorTechnology.					
Transported goods:					
Belt properties:					
Adhesive Medium adhesion Accumulating Other:					
Adnesive Medium a	Accumulating Other:				



Request Form - Timing Belt Conveyor

90° 180° 180°	270° 0° 90°	Terminal box position: 0° 90° 180° 270°	90° 0° 270°		
Thermal contact: Yes		No			
Thermal sensor: Yes		No			
Support Frame					
Yes (assembled)	Yes (supplied I	oose)	No		
Start height [mm]: End height [mm]: Total length [mm]: Incline [°]:	Total length	End height			
Foot type:	Н				
Information / Sketch					