



6ES7222-1BD30-0XB0 S7-1200, SIGNAL BOARD 4 DQ 24VDC 200KHZ

Technical / CAx data

 Technical Data  CAx data**SIMATIC S7-1200, DIGITAL OUTPUT SB 1222, 4DQ, 24VDC 200KHZ****Supply voltages****Power supply to the transmitters**

Supply current, max. 4 mA; per channel

**Current consumption**

from backplane bus 5 V DC, typ. 50 mA

**Power losses**

Power loss, typ. 1 W

**Digital outputs**

Number of digital outputs 4

in groups of 1

Short-circuit protection of the output No

**Switching capacity of the outputs**

with resistive load, max. 0.1 A

**Output voltage**

Rated value (DC) 24 V

for signal "0" (DC), max. 0.1 V; with 10k ohms load

for signal "1", min. 20 V

**Output current**

for signal "1" rated value 0.1 A

for signal "0" residual current, max. 10 µA

**Load resistance range**

upper limit 10 Ω

**Cable length**

Cable length, shielded, max. 50 m

**Interrupts/diagnostics/status information****Alarms**

Alarms Yes

**Diagnoses**

Diagnostic functions Yes

**Degree of protection**

IP20 Yes

**Mechanics**

Plastic Yes

**Dimensions and weight****Dimensions**

Width 38 mm

Height 62 mm

Depth 21 mm

**Weight**

Weight, approx. 40 g

Status Jun 14, 2010